

VOBF Series (Oval, Bellows & Flat)

Features and Strengths

- ✓ Suitable for handling long and narrow objects with flat and curved surfaces
- ✓ Enhancing the adhesion with durable material
- ✓ Stable lifting force can be achieved with this cup for perpendicular and parallel application
- ✓ The feet inside the cup provide an anti-slide



Suitable for Handling

- Automotive panels and door
- Sheet metal
- Press line

Order No.

杭州艾康工业设备

VOBF40X80 PU - 18F

① ② ③

① Size Ø

VOBF30X60	- Ø30X60
• VOBF40X80	- Ø40X80
VOBF55X110	- Ø55X110

② Material


• PU	- Poly Urethane
WPU	- White Poly Urethane

③ Thread size


18M	- G1/8" male (VOBF 30X60, 40X80, 55X110)
• 18F	- G1/8" female (VOBF 30X60, 40X80, 55X110)
14M	- G1/4" male (VOBF 30X60, 40X80, 55X110)
14F	- G1/4" female (VOBF 30X60, 40X80, 55X110)
38F	- G3/8" female (VOBF 30X60, 40X80, 55X110)
12F	- G1/2" female (VOBF 40X80, 55X110)
N18M	- NPT 1/8" male (VOBF 30X60, 40X80)
NF18F	- NPSF 1/8" female (VOBF 30X60, 40X80)
N14M	- NPT 1/4" male (VOBF 30X60, 40X80, 55X110)
NF14F	- NPSF 1/4" female (VOBF 30X60, 40X80, 55X110)
NF38F	- NPSF 3/8" female (VOBF 30X60, 40X80, 55X110)
M10M	- M10xP1.5 male (VOBF 30X60, 40X80, 55X110)

Technical Data

Model	Volume (cm ³)	Perpendicular (↑) Lifting Force (kg)	Parallel (→) Lifting Force (kg)	Radius of curvature R (mm)
		-60 kPa	-60 kPa	
VOBF 30X60	11	5.6	5.8	30
VOBF 40X80	22.5	10.1	10.1	40
VOBF 55X110	66.5	18.8	18.3	50



▲ Female



▲ Male

Model	W	L	G	H1	H2	H3	S	SW
VOBF30X60.. - 18M	32	62	G1/8" male	27	20.5	7	6.9	17
VOBF30X60.. - 18F			G1/8" female	31.5	20.5	-		17
VOBF30X60.. - 14M			G1/4" male	27	20.5	8		17
VOBF30X60.. - 14F			G1/4" female	34.5	20.5	-		17
VOBF30X60.. - 38F			G3/8" female	35	20.5	-		22
VOBF30X60.. - N18M			NPT 1/8" male	27	20.5	8.5		17
VOBF30X60.. - NF18F			NPSF 1/8" female	31.5	20.5	-		17
VOBF30X60.. - N14M			NPT 1/4" male	27	20.5	10.9		17
VOBF30X60.. - NF14F			NPSF 1/4" female	34.5	20.5	-		17
VOBF30X60.. - NF38F			NPSF 3/8" female	35	20.5	-		22
VOBF30X60.. - M10M			M10XP1.5 male	27	20.5	12		17
VOBF40X80.. - 18M	42	82	G1/8" male	29.4	23	7	9	17
VOBF40X80.. - 18F			G1/8" female	33.9	23	-		17
VOBF40X80.. - 14M			G1/4" male	29.4	23	8		17
VOBF40X80.. - 14F			G1/4" female	36.9	23	-		17
VOBF40X80.. - 38F			G3/8" female	37.4	23	-		22
VOBF40X80.. - 12F			G1/2" female	42.4	23	-		25
VOBF40X80.. - N18M			NPT 1/8" male	29.4	23	8.5		17
VOBF40X80.. - NF18F			NPSF 1/8" female	33.9	23	-		17
VOBF40X80.. - N14M			NPT 1/4" male	29.4	23	10.9		17
VOBF40X80.. - NF14F			NPSF 1/4" female	36.9	23	-		17
VOBF40X80.. - NF38F			NPSF 3/8" female	37.4	23	-		22
VOBF40X80.. - M10M			M10XP1.5 male	29.4	23	12		17
VOBF55X110.. - 18M	57	112	G1/8" male	36.5	30	7	12	17
VOBF55X110.. - 18F			G1/8" female	41	30	-		17
VOBF55X110.. - 14M			G1/4" male	36.5	30	8		17
VOBF55X110.. - 14F			G1/4" female	44	30	-		17
VOBF55X110.. - 38F			G3/8" female	44.5	30	-		22
VOBF55X110.. - 12F			G1/2" female	49.5	30	-		25
VOBF55X110.. - N18M			NPT 1/8" male	36.5	30	8.5		17
VOBF55X110.. - NF18F			NPSF 1/8" female	41	30	-		17
VOBF55X110.. - N14M			NPT 1/4" male	36.5	30	10.9		17
VOBF55X110.. - NF14F			NPSF 1/4" female	43	30	-		17
VOBF55X110.. - NF38F			NPSF 3/8" female	44.5	30	-		22
VOBF55X110.. - M10M			M10XP1.5 male	36.5	30	12		17

[Measure Unit : mm]